

ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

CR 900 2X — CR 1200 2X

Automatic spray washer, with double tank for washing and rinsing and motorized rotating basket.

Suitable for medium-sized heavy parts.



Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA)

Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com

 ellegelle.machinery



ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

CR 900 2X — CR 1200 2X


Automatic industrial spray washing machine, double tank, with motorized rotating basket, entirely made of Aisi 304 stainless steel with supporting structure in steel tubulars.

Washing is carried out with a solution of water and detergent at a temperature adjustable from 0 ° to 60 ° by crossing a spray ramp arranged above, below and on the side of the basket. The filtered washing solution is collected in the tank and reused until it is completely exhausted.

The rinsing / passivation phase takes place with the pump, the spray ramp and the separate water recovery tank. The machine is equipped with 2 basket filters externally positioned, both on the washing and rinsing areas, in order to facilitate maintenance and cleaning operations. Loading operations take place in front of the machine by manually opening the tailgate, assisted opening by 2 gas springs. The machine is equipped as standard with a PLC touch screen with programmable functions: time and temperature for washing, rinsing and drying. Level alarms and clogged filters, energy saving ON / OFF function, timer for programmed switching on washing and rinsing heaters.

Options :

- Oil skimmer
- Drying with hot air oven
- Ultrafilter from 100 up to 5 microns
- Electric fan for steam extraction
- Insulation for 80 ° C temperature
- Emptying diaphragm pump
- Basket extraction on external carts
- Reduction baskets
- Automatic opening with pneumatic pistons



TECHNICAL DATA:

CR 900-2X

Dimensions :	1390x 2200 H1370
Basket :	diameter 900 mm, H 550 mm
Payload:	400 kg
Washing pump :	1,5 Kw, 110 l/min
Rinsing pump :	1,5 Kw, 110 l/min
Pressure :	4 bar
Washing tank :	130 lt
Rinsing tank :	130 lt
Washing heat :	2 heaters 4 kw each
Rinsing heat :	2 heaters 4 kw each
Temperature :	adjustable 0° à 60° (80°C insulated)
Motorized rotation :	5 r/min
Alarm :	Low level/ filter clogged

CR1200-2X

Dimensions :	760x 2700 H 1420
Basket :	diameter 1200 mm, H 630 mm
Payload:	600 kg
Washing pump :	2,2 Kw, 200 l/min
Rinsing pump :	2,2 kw, 200 l/min
Pressure :	4 bar
Washing tank :	220 lt
Rinsing tank :	220 lt
Washing heat :	3 heaters 4 Kw each (12 kw)
Rinsing heat :	3 heaters 4 Kw each (12 kw)
Temperature :	adjustable 0-60°C (80°C insulated)
Motorized rotation :	5 r/min
Alarm :	Low level/ filter clogged

(The technical data are not binding. Ellegelle reserves the right to make all variations and modifications, without prior notice, to the products and information contained in this catalog)

Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA)
Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com

 ellegelle.machinery

