ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

Combined parts washer for automatic and manual spray washing Positioned automatic washing for heavy and delicate parts, manual washing with a high pressure lance.



ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

Lower chamber for automatic spray washing.

Single-stage, automatic part-washer suitable for heavy and delicate parts with high resistant greasy contamination. The machine, entirely made of Aisi 304 stainless steel, is equipped with a sturdy full-extension basket suitable for front loading with winch or bridge crane. The washing chamber is provided with a series of sprinklers arranged in a ring above, below and at the side of the loading platform while the basket, which is stopped during the washing phase, can be equipped with nozzles which are adjustable in position for a dedicated washing in the greater need points.

The standard external paneling allows to raise the washing temperature up to 80 ° C with minimum energy expenditure. The basket filter outside the machine ensures easy cleaning and easy maintenance. The machine is complete with electric fan and condensate chamber for steam extraction.


Upper chamber for manual washing:

Equipped with auxiliary pump at 12 bar of pressure and spray lance with solid nylon handle, suitable for quick washing of single pieces. Very thick transparent PVC cover with manual flap opening; provided with compressed air blade in order to guarantee the perfect visibility of the objects during all the washing phases; rubber gloves; spray gun for washing, drying brush and gun with compressed air.

Optional:

800

- Hot air oven
- Ultrafilter from 100 up to 5 microns C
- Coalescence oil separator
- Emptying diaphragm pump
- Electric fan for steam suction



TECHNICAL DATA:

Dimensions: Auto. washing chamber : Useful load : Pump:

1650 x 1440 H 1570 760x760 h475 150 kg

adjustable 0 à 80°C

3 heaters 3 Kw each

4 bar

150 lt

Man. washing chamber: 1070 x 490 h410 Pump for spray lance : de 2,2 Kw 15 l/min Pressure : 12 bar low level / filter Alarm :

Pressure : Temperature : Basket: Heat :

2,2 Kw, 200 l/min vert.

clogged

(The technical data are not binding. Ellegelle reserves the right to make all variations and modifications, without prior notice, to the products and information contained in this catalog)

Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA) Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com



Sellegelle.machinery