

ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

GE 1200 - GE 1500

Single-stage automatic spray washer, with an on-stand removable rotary table or an external trolley. Opening with pneumatic pistons, suitable for very heavy and bulky parts.



Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA)

Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com



ellegelle.machinery



ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

GE 1200 - GE 1500

Single-stage industrial automatic spray washer with motorized rotating basket, entirely made of stainless steel with tubular bearing structure

Washing is carried out with a solution of water and detergent by crossing two spray ramps. Each ramp consists of lower, lateral and upper piping and is powered by a vertical pump with a liner, shaft, diffuser and impeller in aisi 304/316 stainless steel, maintenance-free pump. The washing temperature reaches 80°C with minimum energy expenditure thanks to the complete insulation paneling and it is a guarantee of an excellent result in washing even dry grease with considerable resistance. This temperature also facilitates rapid drying of the piece. The solution is collected in the tank and reused until it is completely exhausted. The machine is equipped with an external basket filter so as to facilitate maintenance operations. The loading operations take place in front of the machine by opening the door with pneumatic pistons and bi-manual push-button panel.

Optional

- Basket extraction on trolley
- Automatic basket extraction
- Drying oven
- Diaphragm emptying pump
- Coalescence oil separator
- Ultrafiltration from 100 up to 5 microns
- Automatic water / detergent load
- Side door for manual washing with a lance



TECHNICAL DATA:

	GE 1200	GE 1500
Dimensions :	L2100 x P1870 h 2100	L2520 x P2150 h 2100
Loading basket :	Diameter 1200 mm H utile 950 mm	Diameter 1500mm H utile 920mm
Max loading :	1200 kg	1500 Kg
Washing pump :	4 Kw, 350 l/min	5,5Kw, 400 l/min
Pressure :	4 bar	4 bar
Tank :	420 l	650l
Heat :	4 heaters 4 Kw each	6 4 heaters 4 Kw each
Temperature :	adjustable 0-80°C	adjustable 0÷80°C
Alarm :	Low level/ filter clogged	Low level/ filter clogged

The technical data are not binding. Ellegelle reserves the right to make all variations and modifications, without prior notice, to the products and information contained in this catalog

Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA)
Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com

 ellegelle.machinery

