

ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

GE 1800-2X GE 2000-2X

Spray washer, with double tank for washing and rinsing, with on-stand removable rotating basket. Opening with pneumatic pistons, suitable for very heavy and bulky parts.



Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA)

Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com



ellegelle.machinery



ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

GE 1800-2X GE 2000-2X

Industrial automatic double-tank spray washer, with motorized rotating basket, entirely made of stainless steel with tubular bearing structure.

Washing is carried out with a solution of water and a biodegradable detergent by crossing a spray ramp fed by a vertical pump with stainless steel aisi 304/316 jacket, shaft, diffuser and impeller, maintenance-free pump. The washing temperature reaches 80°C with minimum energy expenditure thanks to the complete insulation paneling and it is a guarantee of an excellent result in washing even dry grease with considerable resistance. This temperature also facilitates rapid drying of the piece. The solution is collected in the tank and re-used until its complete exhaustion.

Rinsing occurs in the same way as with the washing machine but with a separate tank, pump and piping. The machine is equipped with an exchange system suitable for keeping the washing water separate from the rinsing water.

Loading operations take place in front of the machine by opening the door with pneumatic pistons and bi-manual push-button panel.

Optional

- Manual extraction of basket on exterior trolleys
- Automatic basket extraction on support
- Drying with hot air oven
- Emptying diaphragm pump
- Oil skimmer
- 100 to 5 micron ultrafiltration
- Automatic water/cleaning loading product



CARACTÉRISTIQUES TECHNIQUES :

	GE 1800-2X	GE 2000-2X
Dimensions :	L2550 x P3200 h 2500	L2800 x P3800 h 2500
Loading basket :	Diameter 1800 mm H 920 mm	2000 h useful 1100
Load max :	1800 kg	2000 kg
Washing/Rinse pump:	7,5 Kw + 5,5 kw	7,5 Kw + 5,5 kw
Pressure:	4 bar	3,5 bar
Tank :	800 l +800 l	1100 l +1100 l
Heat :	36+36 Kw	42+42 Kw
Temperature :	adjustable 0÷80°C	adjustable 0-80 °C
Alarm :	Low level/ filter clogged	Low level/ filter clogged

The technical data are not binding. Ellegelle reserves the right to make all variations and modifications, without prior notice, to the products and information contained in this catalog

Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA)
Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com

 ellegelle.machinery

