

ELLEGELLE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

IFP 800 - 1200 - 1700

Immersion metal parts washer with a pneumatic piston up-down basket. Immersion washing with stirring and fluxing, for cleaning pipes and internal parts with complex geometry.




Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA)

Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com

 ellegelle.machinery



ELLEGELE Machinery

CONSTRUCTION AND SALE OF STAINLESS STEEL WASHING MACHINE

IFP 800 - 1200 - 1700

Double-walled and single-stage automatic machine, suitable for immersion washing with flushing and up-down movement of the basket using pneumatic pistons. This movement combined with the flushing phase allows the removal of chippings and dirt even in the innermost parts of the holes, cavities and internal washing of tubes of various sections.


Washing takes place in 2 phases with water and biodegradable detergent at a maximum temperature of 80°C:

- immersion phase fed by a vertical pump immersed in aisi 304/316 stainless steel jacket, shaft, diffuser and impeller. Fluxing with continuous turbulence of the washing lavage to facilitate the penetration and removal of dirt, oil, chippings, grease even in the internal parts
- emerged phase with spray cleaning through high-impact cone nozzles to eliminate the deposit of dirt on the surfaces.

The machine is equipped with an external basket filter so as to facilitate maintenance and cleaning operations. The loading operations take place in front of the machine through the opening and tilt of a stainless steel door and the insertion of the appropriate basket for small parts.

Optional:

- Coalescence oil separator
- Hot air oven drying
- Ultrafilter from 100 to 5 microns
- Diaphragm pump for tank emptying
- Automatic water/detergent load



TECHNICAL DATA:

	IFP800	IFP 1200	IFP 1700
Dimensions :	1570x1950 h2050	2550x 2050 h 2300 mm	3280x2240 h 2300
1 basket :	800x470 h utile 360	1220x 690 h utile 450	1730x670 h 400
Vertical washing pump :	2,2 Kw 200 l/min	4 Kw, 400 l/min	5,5 Kw, 600 l/min
Tank :	530 l	1250 l	1750 l
Heat :	4 de 6 Kw each	8 de 6 Kw each	10r 6 Kw each
Temperature :	réglable 0-80°C	réglable 0÷80°C	réglable 0-80°C
Max basket load :	200 kg	300 kg	500 kg
Alarm :	Low level	Low level	Low level

(The technical data are not binding. Ellegelle reserves the right to make all variations and modifications, without prior notice, to the products and information contained in this catalog)

Ellegelle machinery srl

Via G. Falcone, 41 - 21040 Gerenzano (VA)
Tel. 02 96489596 - 02 9682124

info@ellegellemachinery.com - www.ellegellemachinery.com

 ellegelle.machinery

